


**Plug PowerTOP plus**  
Part no. 3308




- highly heat resistant contact carrier
- frame terminals
- nickel plated contacts
- cable gland and sealing
- strain relief and protection against kinking

**Technical specifications**

|                           |   |
|---------------------------|---|
| Ampere                    | 63 A  |
| Poles                     | 4 p   |
| Voltage                   | 400 V   |
| Clock position            | 6 h   |
| Hertz                     | 50-60 Hz  |
| Connection technology     | Screw terminals   |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 67   |
| Weight                    | 800 g   |
| Declaration of Conformity | VDE, EAC, CQC   |

**Drawing**



| Drawing<br>2 MB 227                  | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                                      |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm                           | a             | 250 | 250 | 250 | 290 | 290 | 290 |
|                                      | Øb            | 111 | 111 | 111 | 128 | 128 | 128 |
|                                      | Øy [max]      | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross             |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm <sup>2</sup> ) min.-max. |               | -16 | -16 | -16 | -50 | -50 | -50 |