



Service

DK

KV

Mi

MC

LES

HENPAS

Technical data

References/Types



In areas with an explosive atmosphere within the European Union only materials that comply with EU directive 94/9/EG (ATEX 100a) must be installed and meet with the corresponding national standards and regulations.

Selection of equipment:

1. The proprietor specifies the separation into explosive areas (dust/gas), the zones and the type of material (atmosphere/dust) with flash point, ignition temperature, conductive or non-conductive.
2. This information must be used to define the requirements in regard to selecting the right equipment.
3. The device ID must provide information about where and in which areas the equipment must be used (device category and, consequently, allocation to the hazard zone).



Degree of protection IP 65 using cable glands AXM.. available as an accessory



Stainless steel cover screws with quick fastening metric thread. Reducing cover fixing time.

**ATEX E-mail:
info@hensel-atex.de
www.hensel-atex.de**

Service



- in accordance with ATEX 100a
- with terminals
- Protection type EExn IIA 3GD T 80° C (T6)
- rated insulation voltage AC 690 V
- degree of protection IP 65
- material impact-resistant thermoplastic
- colour black, RAL 9011

DK



KX 2025 **1.5-2.5 mm², Cu, 3~** **4 mm², Cu, 1~**

5-pole,
6 x 1.5 mm² sol, 4 x 2.5 mm² sol,
3 x 4 mm² sol,
cable entry: order AXM separately





KV




KX 2045 **1.5-4 mm², Cu, 3~** **6 mm², Cu, 1~**

5-pole,
6 x 1.5 mm² sol, 4 x 2.5 mm² sol,
3 x 4 mm² sol, 2 x 6 mm² sol,
cable entry: order AXM separately





Mi



KX 2065 **2.5-6 mm², Cu, 3~** **10 mm², Cu, 1~**

5-pole,
4 x 2.5 mm² sol, 4 x 4 mm² sol,
3 x 6 mm² sol, 2 x 10 mm² sol,
cable entry: order AXM separately





MC



KX 2105 **4-10 mm², Cu, 3~** **16 mm², Cu, 1~**

5-pole,
6 x 2.5 mm² sol, 4 x 4 mm² sol,
4 x 6 mm² sol, 4 x 10 mm² sol, 2 x 16 mm² s
cable entry: order AXM separately





LES



KX 2255 **10-25 mm², Cu, 3~** **35 mm², Cu, 1~**

5-pole,
6 x 10 mm² sol, 4 x 16 mm² s,
4 x 25 mm² s, 2 x 35 mm² s,
cable entry: order AXM separately



Technical data

References/Types