

Technical data sheet

Cap nut cable gland, EX area, metric thread, black

Art.-Nr. 2050374



Cable gland with EG design type approval certificate for products and protection systems for use in accordance with the regulations in explosion-hazard area. Directive 94/9/EC
EC design type approval certificate number: PTB 99 ATEX 3112X and ... 3113X.
With metric connecting thread to IEC 423.
Robust cap-nut cable gland with large sealing area, strain relief and torsion protection for high sealing requirements.
Sealing ring of chloroprene/nitrile rubber, moulded sealing, so no connection thread sealing ring needed. Tested to VDE standards
Protection IP 68 at 5 bar.



PA Polyamide

Master data

Item no.	2050374
Type	VTEC EX M50 SW
Description 1	Cable gland, EX area
Dimension	M50
Colour	Black
Material	Polyamide
Material symbol	PA
Smallest sales unit	5,00 Piece
Weight	9,20 kg/100 pc.


Technical data sheet

Cap nut cable gland, EX area, metric thread, black

Art.-Nr. 2050374



Technical data



Dimension E	68,50 mm
Dimension L min.	42,00 mm
Dimension L max.	57,00 mm
Dimension L1	13,00 mm
Dimension L2	9,00 mm
Dimension L3	32,50 mm
WAF	60,00 mm
Version	Straight
Type of seal	Sealing ring
Bend protection	<input type="checkbox"/>
Sealing range D	24,00 - 37,00 mm
explosion-proof	<input checked="" type="checkbox"/>
Flat cable threaded connection	<input type="checkbox"/>
For Ex zone	Ex area 22
For Ex zone dust	22
Thread	M50 x 1,5
Thread type	Metric
Thread length	13,00 mm
Thread increase	1,50 mm
Nominal thread size	50,00
Fibre-glass reinforced	<input type="checkbox"/>
Halogen-free	<input checked="" type="checkbox"/>
Multiple sealing insert	<input type="checkbox"/>
With locknut	<input type="checkbox"/>
Impact-resistant	<input type="checkbox"/>
Hexagonal corner dimension	68,50 mm
Protection rating	IP68
Splittable gland	<input type="checkbox"/>
max. permitted ambient temperature	-20,00 - 65,00 °C
Strain relief option	<input checked="" type="checkbox"/>