



KV Circuit breaker boxes 3-54 modules



KV 3654

- 54 modules: 3 x 18 x 18 mm
- without PE and N terminal

IP
54




- 3-row
- order PE/N terminals separately
- for the installation of DIN rail equipment up to 63 A, top hat profile 35 mm
- with transparent door
- for door locking device and sealing device refer to accessories
- with cable entry cover
- with blanking strips for unused DIN rail openings
- cable entry via integrated elastic membranes
- degree of protection: IP 54
- colour: grey, RAL 7035


rated insulation voltage	$U_i = 400 \text{ V a.c.}$
power dissipation capability	$P_{de} = 50 \text{ watts at } 30 \text{ K according to EN 60670-24}$
protection class	II
material	PS (Polystyrene)
width	403 mm
height	630 mm
depth	129 mm
weight	4,238 kg

Drawings

Dimension drawing



KV Circuit breaker boxes 3-54 modules




KV 3654

- 54 modules: 3 x 18 x 18 mm
- without PE and N terminal

IP
54

Detail mass



Box walls

- 8xØ7-12 mm

8xØ7-14 mm

4xØ12-20 mm

1xØ16,5-29 mm

8xØM20
- 8xØ7-12 mm

8xØ7-14 mm

4xØ12-20 mm


1xØ16,5-29 mm

8xØM20

Operating and ambient conditions



<p>Application area</p>	<p>IP 54/65 design: Suitable for indoor installation and outdoor installation, protected against weather influences</p> <p>IP 40/41 design: Suitable for installation in dry indoor areas</p> <p>However, pay attention to the climatic effects on the installed equipment , for example, high or low ambient temperatures or formation of condensed water see technical information</p>
-------------------------	--

KV Circuit breaker boxes 3-54 modules



KV 3654

- 54 modules: 3 x 18 x 18 mm
- without PE and N terminal

Ambient temperature	Average value over 24 hours + 35 °C Maximum value + 40 °C Minimum value - 5 °C
Relative humidity	50% at 40° C short-time 100% at 25° C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position
Burning behaviour	Glow wire test IEC 60695-2-11: 750 °C UL Subject 94: V-2 flame-retardant self-extinguishing
Degree of protection against mechanical load	IK08 (5 Joule)
Toxic behaviour	halogen-free silicone-free "halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 60754-2
Note:	For material properties see technical data.